

TS-6M

RF-Gain
S-Meter

cb mobile radio 27 MHz

- RF-Gain
- Priority Channel 9 / 19
- Squelch, automatic & manual
- Full Multi Norm



Full Multi Norm



EBS-TS6M

mounting kit TS-6M



features

- squelch, auto and manual
- RFG - receipt frequency sensitivity
- priority channels 9 and 19
- AM / FM operating mode
- LCD with S-Meter
- rotary channel selector
- up/down microphone with signal key
- jack for external loudspeaker
- 12 V

- connection : 6-pin microphone
PL-antenne
- dimensions : 139 x 40 x 125 mm
- weight : 690 g

versions

TS-6M Full Multi Norm - CB3195

DE	: 80 ch. FM, 4 W / 40 ch. AM, 4 W
EU	: 40 ch. FM, 4 W / 40 ch. AM, 1 W
EC	: 40 ch. FM, 4 W
EI	: 40 ch. FM, 4 W / 40 ch. AM, 4 W
PL	: 40 ch. FM, 4 W / 40 ch. AM, 4 W
UK	: 40 ch. FM, 4 W (UK) / 40 ch. FM 4 W (EC)

TS-6M-c CEPT version - CB3196

40 channels FM, 4 W

contents

- 1x TS-6M
- 1x up/down microphone with signal key
- 1x under-dash-mounting-kit,
- 1x power supply cable
- 1 x manual